Rain Harvesting
www.rainharvesting.com

Provided by: Rain Harvesting Supplies, Inc.
www.rainharvestingsupplies.com

leaf eater ADVANCED

MOZZIE PREVENTION

The Next Generation in Rain Heads!

- Advanced debris shedding technology
- Designed to prevent water shedding
- High flow rate performance
- Self cleaning
- Low maintenance

Prevent leaves and debris from entering your Rain Harvesting System

Suitable for vertical and horizontal (rear outlet) pipe installations

VH pivot OUTLET

FITS 4" round downspouts (adaptor included)

clean shield™
NEXT GENERATION TECHNOLOGY

Next generation technology for advanced debris shedding.

- ✓ Directs leaves & debris away from the flow of water
- ✓ Improves tank water quality
- ✓ Single screen for easy installation
- ✓ Self cleaning - low maintenance
- ✓ 1/32" aperture stainless steel mosquito proof screen
- ✓ Superior flow rate - collect more rainwater



VH pivot OUTLET™

VH Pivot Outlet makes installation easy!

- Pivot the outlet to suit vertical or horizontal (rear outlet) downspout
- One product adaptable to different installations.
- Rubber o-ring included for water tight seal



Horizontal Position

Vertical Position

Rain Harvesting™
www.rainharvesting.com

Rain Harvesting Pty Ltd, 1005 N Common Drive Aurora, Illinois 60504
Toll Free: +1 866 506 3047 | Ph: +1 (630) 405 – 0579 | Fax: +1 (630) 851 – 7744
info@rainharvesting.com | Made in China

PO300

9317118999876
9 317118 010229

INSTALLATION INSTRUCTIONS

GUTTER & MID-MOUNT INSTALLATION

STEP 1 **Gutter:** Measure 8" from the underside of the gutter and remove this section of downspout. Ensure the cut edge is clean and smooth.

Mid-Mount: Remove 8" of downspout where the Leaf Eater Advanced™ is to be situated. Ensure all cut edges are clean and smooth. **(FIGURE 1)**

STEP 2 Using the quick release tabs remove the Cleanshield™ screen by lifting it up and then out. **(FIGURE 2)**

STEP 3 Insert the Leaf Eater Advanced™ by sliding it up over the cut section and then down into position. The Leaf Eater Advanced™ outlet should be slid firmly onto the bottom downspout until it can be pushed no further. **(FIGURE 3)**

STEP 4 Screw the Leaf Eater Advanced™ into position through the screw slots provided. Ensure appropriate screws and anchors (if required) are used. **(FIGURE 5)**

STEP 5 Insert the Cleanshield™ screen into the Leaf Eater Advanced™. Ensure the Cleanshield™ screen is sitting firmly in place and check installation is secure. **(FIGURE 6)**

HORIZONTAL (REAR OUTLET) INSTALLATION

STEP 1 Using the quick release tabs remove the Cleanshield™ screen by lifting it up and then out. **(FIGURE 2)**

STEP 2 Swivel the outlet to the horizontal position - some force may be required.

STEP 3 Position the Leaf Eater Advanced™ next to existing pipework, mark and cut top and bottom cut lines as per **FIGURE 4** . Ensure the cut edge is clean and smooth.

STEP 4 Insert the Leaf Eater Advanced™ by sliding the rear outlet into the horizontal pipe. The back fixing plate must sit behind the top section of downspout. **(FIGURE 3)**

STEP 5 Screw the Leaf Eater Advanced™ into position through the screw slots provided. Ensure appropriate screws and anchors (if required) are used. **(FIGURE 5)**

STEP 6 Insert the Cleanshield™ screen into the Leaf Eater Advanced™. Ensure the Cleanshield™ screen is sitting firmly in place and check installation is secure. **(FIGURE 6)**













HANDY HINTS

PAINTING

Remove the Cleanshield™ screen when painting. It is not recommended to paint the frame of the Cleanshield™ screen.

CLEANING

The Cleanshield™ screen is mostly self cleaning. If cleaning is required simply lift the Cleanshield™ screen out by taking hold of the quick release tabs and pull the Cleanshield™ screen upwards and outwards, then hose or brush off.

PROTECTING THE HOME

General stormwater application
Rain Heads help ensure gutters and downspouts do not block up with leaves and debris.