



**ELECTRICAL DATA:**

VOLTS: 208/230      DATE CODE: \_\_\_\_\_

PHASE: 1      LARGEST MOTOR FLA: 28

HZ: 60      SHORT CIRCUIT CURRENT: 5 ka

TOTAL FLA: 35      rms SYMMETRICAL, 230 MAXIMUM

MAX H.P.: 5      PANEL TYPE: 3R

SERVICE DISCONNECT SUPPLIED BY OTHERS  
 USE COPPER OR ALUMINUM CONDUCTORS RATED AT 75 deg CELSIUS  
 TERMINAL BLOCK TORQUE SPECS: 9IN /LB  
 GROUNDING PER N.E.C. GRND LUG TORQUE SPECS: 45IN /LB

THIS PRINT IS THE PROPERTY OF MUNRO PUMP INC., AND IT EMBODIES A PROPRIETARY DESIGN WHICH SHALL NOT BE DISCLOSED, USED OR DUPLICATED FOR PROCUREMENT OR MANUFACTURING PURPOSES UNLESS SPECIFIC WRITTEN AUTHORIZATION BY MUNRO PUMP INC. IS GIVEN. THIS PRINT IS LOANED, SUBJECT TO RETURN UPON DEMAND.

CATALOG NO.	MPSR220AU	<b>MUNRO</b> GRAND JUNCTION, CO 1-877-372-9005
DIAGRAM NO.	MPSR220AU1117-R2	